

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Seapower Inflatable Boat Cleaner
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Product category PC31 Polishes and wax blends
- Process category
PROC0 Other
PROC10 Roller application or brushing
- Environmental release category
ERC10a Widespread use of articles with low release (outdoor)
- Application of the substance / the mixture
See our technical datasheet for application of this product.
Maintenance product for rubber and vinyl surfaces
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
fax +31-(0)297-342078
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!
See manufacturer

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Turpentine, oil

· Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304	25-50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 8006-64-2 EINECS: 232-350-7 Index number: 650-002-00-6 Reg.nr.: 01-2119502456-45	Turpentine, oil Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 2)

Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 3)

- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
see instructions labelling
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

8006-64-2 Turpentine, oil

WEL	Short-term value: 850 mg/m ³ , 150 ppm
	Long-term value: 566 mg/m ³ , 100 ppm

- DNELs

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Dermal	Long-term - systemic effects, worker	300 mg/kg bw/day (Werker/Worker)
Inhalative	Long-term - systemic effects, worker	1500 mg/m ³ (Werker/Worker)

67-63-0 propan-2-ol

Inhalative	Long-term - systemic effects, worker	500 mg/m ³ (Werker/Worker)
------------	--------------------------------------	---------------------------------------

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: nitrile rubber;
recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.
- As protection from splashes gloves made of the following materials are suitable:
Cloropene; handglove thickness > 0.7mm, penetration time > 60min. according EN374.
Nitrilrubber; handglove thickness > 0.3mm, penetration time > 60min. according EN374.
- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/freezing point:	Undetermined.
-------------------------------	---------------

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 5)

Initial boiling point and boiling range:	82 °C
· Flash point:	40 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	220 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.95 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/ water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	80 s (ISO 6 mm)
· Solvent content:	
Organic solvents:	55.8 %
VOC content:	55.8 %
	VOC content:
	529.6 g/l / 4.42 lb/gal
· 9.2 Other information	No further relevant information available.

* **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 6)

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg bw (rat)
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5000 mg/m ³ (vapour) (rat) ((8h))
67-63-0 propan-2-ol		
Oral	LD50	5045 mg/kg bw (rat)
Dermal	LD50	12800 mg/kg bw (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
- Primary irritant effect:
- Skin corrosion/irritation
Based on available data, the classification criteria are not met.
- Serious eye damage/irritation
Causes serious eye irritation.
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity
Based on available data, the classification criteria are not met.
- Carcinogenicity
Based on available data, the classification criteria are not met.
- Reproductive toxicity
Based on available data, the classification criteria are not met.
- STOT-single exposure
Based on available data, the classification criteria are not met.
- STOT-repeated exposure
Based on available data, the classification criteria are not met.
- Aspiration hazard
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy	
ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))
LL50 (96h)	>1000 mg/l ((Onorhynchus mykiss OECD 203))
EbL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))
	100 mg/l ((Pseudo. subcap. growth rate OECD 201))
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish

(Contd. on page 8)

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 7)

- Additional ecological information:
- General notes:
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
ADR, IMDG, IATA UN1993
- 14.2 UN proper shipping name
ADR 1993 FLAMMABLE LIQUID, N.O.S.
IMDG FLAMMABLE LIQUID, N.O.S.
IATA FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL), Naphtha (petroleum), hydrotreated heavy)
- 14.3 Transport hazard class(es)
ADR, IMDG, IATA

· Class 3 Flammable liquids.
· Label 3
- 14.4 Packing group
ADR, IMDG, IATA III

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 8)

- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E, S-E
- Stowage Category A
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.
- Transport/Additional information:
- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
- Maximum net quantity per inner packaging: 30 ml
- Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
- Maximum net quantity per inner packaging: 30 ml
- Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Named dangerous substances - ANNEX I None of the ingredients is listed.
 - Seveso category P5c FLAMMABLE LIQUIDS
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 - National regulations:
 - Technical instructions (air):
- | Class | Share in % |
|-------|------------|
| NK | 50-100 |
- Waterhazard class:
 - Water hazard class 3 (Self-assessment): extremely hazardous for water.
 - 15.2 Chemical safety assessment:
 - A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 27.02.2017

Version number 6

Revision: 27.02.2017

Trade name: Epifanes Seapower Inflatable Boat Cleaner

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids - Category 2
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
Skin Sens. 1: Skin sensitisation - Category 1
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
Asp. Tox. 1: Aspiration hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.