

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: Epifanes Interimcoat Comp. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Product category PC9a Coatings and paints, thinners, paint removers
 - Process category PROC10 Roller application or brushing
 - Environmental release category ERC2 Formulation into mixture
- Application of the substance / the mixture
See our technical datasheet for application of this product.
Curing component of a two-component intermediate primer
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
fax +31-(0)297-342078
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!
Zie onder fabrikant/leverancier

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Polyaminoamide

4-methylpentan-2-one

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

Resin mixture

Solvent mixture with pigment additives

Mixture of reactive synthetic binder and organic solvents

· Dangerous components:

CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one	25-50%
	Flam. Liq. 2, H225 Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	
	Polyaminoamide	25-50%
	Flam. Liq. 3, H226 Eye Dam. 1, H318	

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225	≤ 2.5%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤ 2.5%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment:
Wear fully protective suit.
Mouth respiratory protective device.

GB

(Contd. on page 4)

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 3)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Wear protective clothing.
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Work only in fume cupboard.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.
- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

108-10-1 4-methylpentan-2-one

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	104 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 15 min. / Exposure time	208 mg/m ³ (Algemene bevolking/ General population)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 4)

1330-20-7 xylene

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	210 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 15 min. / Exposure time	442 mg/m ³ (Algemene bevolking/ General population)

78-93-3 butanone

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	590 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 15 min. / Exposure time	900 mg/m ³ (Algemene bevolking/ General population)

108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm
	Sk, BMGV

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
	Sk, BMGV

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

• DNELs
1330-20-7 xylene

Dermal	Long-term - local effects, worker	180 --- (Werker/Worker)
Inhalative	Acute-local effects, worker	289 mg/m ³ (Werker/Worker)
	Acute - systemic effects, worker	289 mg/m ³ (Werker/Worker)
	Long-term - local effects, worker	77 mg/m ³ (Werker/Worker)

• PNECs
1330-20-7 xylene

Aquatic compartment - freshwater	0.327 mg/L (not specified)
Aquatic compartment - marine water	0.327 mg/L (not specified)
Aquatic compartment - water, intermittent releases	0.327 mg/L (not specified)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (not specified)
Terrestrial compartment - soil	2.31 mg/kg dw (not specified)
Sewage treatment plant	6.58 mg/L (not specified)

• Ingredients with biological limit values:
108-10-1 4-methylpentan-2-one

BMGV	20 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: 4-methylpentan-2-one

(Contd. on page 6)

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 5)

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- Respiratory protection:
Suitable respiratory protective device recommended.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter AX
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:
Butyl rubber, glove thickness 0.7 mm, > 480 min breakthrough time / permeation to EN374.
- As protection from splashes gloves made of the following materials are suitable:
Nitrile
Glove thickness > 0.45 mm, breakthrough time > 30 min. to EN374

(Contd. on page 7)

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 6)

- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	79 °C
- Flash point: <21 °C
- Flammability (solid, gas): Not applicable.
- Ignition temperature: 460 °C
- Decomposition temperature: Not determined.
- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits:

Lower:	1.1 Vol %
Upper:	9.0 Vol %
- Vapour pressure at 20 °C: 8 hPa
- Density at 20 °C: 0.88753 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with water: Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water: Not determined.
- Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	30 s (ISO 4 mm)
- Solvent content:

Organic solvents:	57.8 %
-------------------	--------

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 7)

VOC content:	57.8 %
	VOC content: 512.8 g/l / 4.28 lb/gl
Solids content:	40.0 % (VB% 1h150 C)
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

108-10-1 4-methylpentan-2-one

Oral	LD50	2080 mg/kg bw (rat)
Dermal	LD50	16000 mg/kg bw (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg bw (rat)
Dermal	LD50	2000 mg/kg bw (rabbit)

78-93-3 butanone

Oral	LD50	3300 mg/kg bw (rat)
Dermal	LD50	5000 mg/kg bw (rabbit)

64-17-5 ethanol

Oral	LD50	7060 mg/kg bw (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye damage.
- Respiratory or skin sensitisation
Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity
Based on available data, the classification criteria are not met.
- Carcinogenicity
Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 8)

- Reproductive toxicity
Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause respiratory irritation.
- STOT-repeated exposure
Based on available data, the classification criteria are not met.
- Aspiration hazard
Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

1330-20-7 xylene

EC50 1 mg/l (daphnia magna) (48 uur/hour)

LC50 13.5-2.6 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

1330-20-7 xylene

Log Kow 3 (not specified)

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

08 01 00	wastes from MFSU and removal of paint and varnish
----------	---

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.



GB

(Contd. on page 10)

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 9)

SECTION 14: Transport information

• 14.1 UN-Number	UN1263
• ADR, IMDG, IATA	
• 14.2 UN proper shipping name	1263 PAINT RELATED MATERIAL
• ADR	PAINT RELATED MATERIAL
• IMDG, IATA	
• 14.3 Transport hazard class(es)	
• ADR	
	
• Class	3 (F1) Flammable liquids.
• Label	3
• IMDG, IATA	
	
• Class	3 Flammable liquids.
• Label	3
• 14.4 Packing group	
• ADR, IMDG, IATA	III
• 14.5 Environmental hazards:	
• Marine pollutant:	No
• 14.6 Special precautions for user	Warning: Flammable liquids.
• Danger code (Kemler):	30
• EMS Number:	F-E, S-E
• Stowage Category	A
• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
• Transport/Additional information:	
• ADR	
• Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• Transport category	3
• Tunnel restriction code	D/E
• IMDG	
• Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 10)

- UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	50-100
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
- Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent

(Contd. on page 12)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 24.02.2017

Version number 5

Revision: 24.02.2017

Trade name: Epifanes Interimcoat Comp. B

(Contd. of page 11)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

— GB —